

Model *εSENSE*[™]

Carbon dioxide transmitter

PRODUCT DESCRIPTION

εSENSE[™] is a new simple, low cost, state-of-the-art, infrared and maintenance-free carbon dioxide transmitter for installation in the climate zone or in the ventilation duct.

εSENSE[™] measures the carbon dioxide concentration in the ambient air up to 2000 ppm and transforms the data into an analogue output.

εSENSE[™] helps you save money by decreasing your energy consumption while creating a healthier indoor climate!



New!

FEATURES

SenseAir's patented state-of-the-art gold-plated infrared (NDIR) waveguide technology offers reliable measurements

- Measurement range: 0 - 2 000 ppm CO₂
- Two analogue outputs (not model -I):
- Internal automatic self-diagnostics.
- Maintenance-free in normal applications
- Cost-optimized for connection to DDC:s
- Prepared for complementary passive temperature element (model -Tr).
- Different housing options

APPLICATIONS

εSENSE[™] is an extremely cost-optimized sensor solution for climate control of buildings and other processes.

By controlling the ventilation based on actual demand, it helps you decrease your energy consumption and yet have a healthy indoor climate!

The different housing options makes the *εSENSE*[™] available to almost any application or environment for example in greenhouses, residential and commercial buildings.

εSENSE[™] -Tr is also prepared for quick mounting of a complementary passive temperature element, which can easily be done by the customer.

εSENSE[™] II fits directly on top of American standard electrical wall conduits

eSENSE™ carbon dioxide transmitter Technical Specification* (rev nr: 040305)

General Performance

Compliance with	EMC directive 89/336/EEC. RoHS directive 2002/95/EG
Operating Temperature Range	0 - 50 °C
Storage Temperature Range	-40 to +70 °C (display model -D: -20 to +70 °C)
Operating Humidity Range	0 to 95% RH (non-condensing)
Operating Environment	residential, commercial and industrial spaces ¹
Warm-up Time	≤ 1 min. (@ full specs ≤ 15 minutes)
Sensor Life Expectancy	> 15 years
Maintenance Interval	no maintenance required ²
Self Diagnostics	complete function-check, LCD error indication (display model -D)
Display (model -D)	4 Digits, 7 segments LCD with ppm indicator

Electrical

Power Input	24 VAC/VDC ±20%, 50 Hz (half-wave rectifier input)
Power Consumption	< 1 Watt average
Connection screw terminal A	4 x 1,5 mm ² for power input (G+, G0) and voltage outputs (OUT1, OUT2)
Connection screw terminal B	2 x 1,5 mm ² for passive resistive output (Y, M) for option -Tr
Model IP50	34 cm 3-wire pigtail. Please note that OUT2 is not made available.

CO₂ Measurement

Sensing method	Gold-plated infrared (NDIR) waveguide technology with Automatic Background Calibration (ABC) and passive gas diffusion (no moving parts)
Response Time (T _{1/e})	< 10 sec. @ 30 cc/min. flow rate , < 3 min. diffusion time
Repeatability.....	± 20 ppm ± 1 % of reading
Accuracy ²	± 30 ppm ± 3 % of reading
Annual Zero Drift ²	< ± 10 ppm
Pressure Dependence	+ 1.6 % reading per kPa
Measurement range	0 - 3 000 ppm

Outputs

Voltage signal terminal CO₂ ³

OUT1 linear conversion range.....	0 -10 VDC for 0 - 2 000 ppm.
OUT2 linear conversion range.....	0 – 10 V, 2 - 10, 0 - 20, 4 - 20 mA
.....	D/A resolution 10 bits, 10 mV
D/A conversion accuracy	± 2 % of reading ± 50 mV
Electrical characteristics.....	R _{OUT} < 100 Ohm, R _{LOAD} > 5 kOhm

Resistive terminals ⁴

Thermistor outputs	temperature measurement resistor terminal output with signal return connected to ground terminal (option -Tr)
--------------------------	---

Housing options

WALL HOUSING (standard) With or without display.
eSENSE: Dim.: 100 x 80 x 28 mm (H x W x D)
Protection class: IP30
60 mm hole separation for European standard J-boxes.

eSENSE II: Dim.: 130 x 85 x 30 mm (H x W x D)
Protection class: IP30
Fits Us standard J-boxes.



eSENSE™ -D

eSENSE™ -D II

INDUSTRIAL WALL HOUSING
With or without display
Dim.: 142 x 84 x 46 mm (H x W x D)
Protection class: IP54

DUCT HOUSING (model -K)
Protection class: IP65
Duct probe length: 245 mm (model -K)
(adjustable according to duct dimension)



eSENSE™ -K-D

eSENSE™ IP54

ALL-ROUND HOUSING (model -IP50)
Dim.: 106 x 67 x 26 mm (H x W x D)
Protection class: IP50
Connection: 34 cm 3-wire pigtail (no OUT2)
For both wall and duct applications.



eSENSE™ -IP50

Note 1: The SO₂ enriched environments are excluded.

Note 2: In normal IAQ applications (@ NTP). Accuracy is defined after minimum 3 weeks of continuous operation. The tolerance of the span calibration gas (2 % unless otherwise requested) and test gas adds to the total uncertainty.

Note 3: The specifications are valid for the output load connected to ground G0. Other outputs and measurement ranges are available per request.

Note 4: Resistive probe is to be mounted by the user. Can be factory pre-mounted upon request.

* Can be changed without notice