



Trójnik Geberit Mapress C-Stahl z gwintem wewnętrznym i końcówkami wsuwanymi



Ilustracja przykładowa

CHARAKTERYSTYKA

- Ocynkowany zewnętrznie

DANE TECHNICZNE

Materiał

Stal nierostowa 1.0034 E195
(EN 10305)

| Nr art. | DN | d_1, \varnothing mm | Rp " | $d1, \varnothing$ mm | arc ° | L cm | L1 cm | H cm | H1 cm | Z cm |
|---------|---------|--------------------------|---------|-------------------------|----------|---------|----------|---------|----------|---------|
| 21341 | 15 | 18 | 1/2 | 18 | 90 | 10 | 3.4 | 5 | 5 | 2.1 |
| 21342 | 20 / 15 | 22 | 1/2 | 22 | 90 | 10 | 3.6 | 5 | 5 | 2.3 |
| 21343 | 25 / 15 | 28 | 1/2 | 28 | 90 | 10 | 4.3 | 5 | 5 | 3 |
| 21344 | 32 / 15 | 35 | 1/2 | 35 | 90 | 11.4 | 4.7 | 5.7 | 5.7 | 3.4 |
| 21345 | 40 / 15 | 42 | 1/2 | 42 | 90 | 13.4 | 5 | 6.7 | 6.7 | 3.7 |
| 21346 | 50 / 15 | 54 | 1/2 | 54 | 90 | 14.6 | 5.7 | 7.3 | 7.3 | 4.4 |