

Product datasheet: Room heater to regulation (EU) no. 811/2013

		HPA-O 13 Premium
		238982
Manufacturer		STIEBEL ELTRON
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Energy efficiency class for central heating in moderate climates for low temperature applications		A+++
Rated heating output in moderate climates for average temperature applications (Prated)	kW	15
Rated heating output in moderate climates for low temperature applications (Prated)	kW	15
Seasonal room heating efficiency in moderate climates for average temperature applications (ηs)	%	141
Seasonal room heating efficiency in moderate climates for low temperature applications (ηs)	%	182
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	8620
Annual energy consumption in moderate climates for low temperature applications (QHE)	kWh/a	6689
Sound power level external	dB(A)	54
Rated heating output in colder climates for average temperature applications (Prated)	kW	22
Rated heating output in colder climates for low temperature applications (Prated)	kW	21
Rated heating output in warmer climates for average temperature applications (Prated)	kW	8
Rated heating output in warmer climates for low temperature applications (Prated)	kW	8
Seasonal room heating efficiency in colder climates for average temperature applications (η s)	%	130
Seasonal room heating efficiency in colder climates for low temperature applications (\(\Gamma\)s)	%	159
Seasonal room heating efficiency in warmer climates for average temperature applications (ηs)	%	163
Seasonal room heating efficiency in warmer climates for low temperature applications (Π s)	%	219
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	16285
Annual energy consumption in colder climates for low temperature applications (QHE)	kWh/a	12796
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	2581
Annual energy consumption in warmer climates for low temperature applications (QHE)	kWh/a	1930



IJA ENERG енергия · ενεργεια

STIEBEL ELTRON

HPA-O 13 Premium



































G



2015 811/2013

Product datasheet: Composite system consisting of room heater and temperature controller to regulation (EU) no. 811/2013

		HPA-O 13 Premium
		238982
Manufacturer		STIEBEL ELTRON
Seasonal room heating efficiency in moderate climates for average temperature applications (Γs)	%	141
Temperature controller class		VI
Contribution of temperature controller to room heating energy efficiency	%	4
Room heating energy efficiency of composite system under moderate climatic conditions	%	145
Room heating energy efficiency of composite system under colder climatic conditions	%	134
Room heating energy efficiency of composite system under warmer climatic conditions	%	167
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	9
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	24
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Room heating energy efficiency class of composite system under moderate climatic conditions		A++

Required details about room heater and combi heater with heat pump to regulation (EU) no. 813/2013 & 811/2013

		HPA-O 13 Premium
		238982
Manufacturer		STIEBEL ELTRON
Heat source		Outside air
With booster heater	· · · · · · · · · · · · · · · · · · ·	x
Combi boiler with heat pump		-
Rated heating output in colder climates for average temperature applications (Prated)	kW	22
Rated heating output in moderate climates for average temperature applications (Prated)	kW	15
Rated heating output in warmer climates for average temperature applications (Prated)	kW	8
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	13.8
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	8.4
$T_{\rm J} = 7$ °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	7.8
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	9
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	12.5
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	13.4
For air/water heat pumps:Tj = -15 °C (if TOL< -20 °C) (Pdh)	kW	13.4
Dual mode temperature in moderate climates (Tbiv)	°C	
Seasonal room heating efficiency in colder climates for average temperature applications (η s)	%	130
Seasonal room heating efficiency in moderate climates for average temperature applications ($\ensuremath{\eta s}$)	% 	141
Seasonal room heating efficiency in warmer climates for average temperature applications (Π s)	% 	163
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		2.48
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		3.51
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		4.61
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		6,66
Tj = dual mode temperature under moderate climatic conditions (COPd)		2.59
Tj = operating temperature limit under moderate climatic conditions (COPd)		2.28
For air/water heat pumps:Tj= -15°C (if TOL< -20 °C) (COPd)		2.28
Operating temperature limit in colder climates (TOL)	°C	-20
Operating temperature limit in moderate climates (TOL)	°C	-10
Operating temperature limit in warmer climates (TOL)	°C	2
Heating water operating temperature limit in colder climates (WTOL)	°C	65
Heating water operating temperature limit (WTOL)	°C	65
Heating water operating temperature limit in warmer climates (WTOL)	°C	65
Power consumption, OFF state (Poff)	<u>W</u>	10
Power consumption, thermostat OFF state (PTO)	<u>W</u>	10
Standby power consumption (PSB)	W	10
Power consumption, operating state, with crankcase heating (PCK)	W	38
Booster heater heating output (PSUB)	kW	0
Type of energy supply, booster heater Power control	<u> </u>	electric
Power control Sound power level external	dB(A)	variable 54
Annual energy consumption in colder climates for average temperature applications (QHE)	kWh/a	16285
Annual energy consumption in moderate climates for average temperature applications (QHE)	kWh/a	8620
Annual energy consumption in warmer climates for average temperature applications (QHE)	kWh/a	2581

Flow rate, heat source side m³/h 4000